

Twirl Motor

● PRODUCT SERIES 产品系列

(Encoders) ME-3237D

双通道磁性译码器

Two Channel Hall Effect Encoder

★ 使用相对湿度: 20%~85% RH


Operating relative humidity

★ 使用温度范围: -40°C~+85°C

Operating temperature range



外形尺寸图/Appearance size



Two Channel Encoder
Connections:

- 1.HALL SENSOR A Vout
- 2.HALL SENSOR B Vout
- 3.HALL SENSOR GND
- 4.HALL SENSOR Vcc

*此译码器主要安装在步进电机, 空心杯电机, 钢管电机。

*The decoder is mainly installed in stepper motor,
hollow cup motor, steel tube motor.

*每周输出3PPR,7PPR,13PPR


*Each turnoutput3PPR,7PPR,13PPR

规格特性 Charac teristics	代号 Symbol	测试条件 Test conditions	极小 Min	基本 Ref	最大 Max	单位 Units
输入电压 Supply Voltage	Vcc	-----	4.5	--	24	V
输入电流 Supply Current	Ice	-----	--	14	20	mA
输出电流 Output Current	Ic	Vce=12V; Gauss<-170	--	<0.1	20	mA
输出漏电电流 Output Leakage Current	Icex	Output open; 25°C [77°F]	--	--	10	μ A
输出上升时间 Output Rise Time	Tr	RL=820Ω; CL=20pF; 25°C	--	0.5	1.5	μ S
输出下降时间 Output Fall Time	Tf	RL=820Ω; CL=20pF; 25°C	--	0.2	1.5	μ S


ELECTRICAL CHARACTERISTICS

At V = 4.5V to 24V with 20mA load with Ta = -40°C to 125°C [-77°F to 257°F] unless otherwise noted.

输出电路/Output Circuit



输出波形/Output Wave



○ The above parameters are for reference only.